


REV.	ECH. NO.	LOCATIONS.	DESCRIPTION	DATE	CHANGER
A				12-9-18	


Specification

Rated Voltage: 100V AC/DC
Rated Current: 1A AC/DC
Contact Resistance: 20mohms max
Insulator Resistance: 1000Megohms/Min.
Dielectric Withstanding: 500V AC
Operating Temperature: -40°C~+105°C
Plastic Material: PA6T,UL94V-0,Black
Contact Material: Brass
Finish: Gold Flash Plated

Ordering information



PIN	A	B
2	1.27	2.54
3	2.54	3.81
4	3.81	5.08
5	5.08	6.35
6	6.35	7.62
7	7.62	8.89
8	8.89	10.16
9	10.16	11.43
10	11.43	12.70
11	12.70	13.97
12	13.97	15.24
13	15.24	16.51
14	16.51	17.78
15	17.78	19.05
16	19.05	20.32
17	20.32	21.59
18	21.59	22.86
19	22.86	24.13
20	24.13	25.40
21	25.40	26.67
22	26.67	27.94
23	27.94	29.21
24	29.21	30.48
25	30.48	31.75
26	31.75	33.02
27	33.02	34.29
28	34.29	35.56
29	35.56	36.83
30	36.83	38.10
31	38.10	39.37
32	39.37	40.64
33	40.64	41.91
34	41.91	43.18
35	43.18	44.45
36	44.45	45.72
37	45.72	46.99
38	46.99	48.26
39	48.26	49.53
40	49.53	50.80
41	50.80	52.07
42	52.07	53.34
43	53.34	54.61
44	54.61	55.88
45	55.88	57.15
46	57.15	58.42
47	58.42	59.69
48	59.69	60.96
49	60.96	62.23
50	62.23	63.50



ITEM	PART NO	SPECIFICATION	Q'ty
1	2-1015XX-015B	1.27mm塑膠1XNP,塑膠高1.5(PA6T)	1PCS
2	5-Q040X173S-G	0.40四方鍍金針,180°長17.3	NPCS

TOLERANCE UNSPECIFIED:	
X	±0.50
XX	±0.25
XXX	±0.10
XXXX	±0.05
X"	±2°
X'X	±1°

PROJECTION:	
UNIT: mm [inch]	SCALE:1:1
SIZE: A4	

APPROVED BY:	DATE:	DRAWN BY:	DATE:
何智权	9-18-12	杨熊	9-18-12
陈宗渊	9-18-12		

TITLE: 成品规格图	
PART NO.	PART NAME: 1.27mm Pin Header
MOLD NO.	1-1015XXSG-010148B
DRAW NO.	A-1-1015XXSG-010148B
SHEET	1 OF 1